



Description

Raytec VAR-PSU-7A4U Outdoor Power Supplies provide 24VAC or 28VAC distributed via four (4) outputs for powering Raytec illuminators and other video accessories.

- Four (4) fuse protected outputs
- 24VAC or 28VAC outputs:
7.25A @ 24VAC or
6.25A @ 28VAC
- NEMA 4/4X, IP66-11 Rated enclosure for outdoor use
- Surge protection
- Spare fuses provided (all models with primary and/or secondary fuses)
- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens
- Lockable stainless steel latches
- Integral flanges simplify wall or pole mounting
- UL Listed in the U.S. and Canada
- CE Approved
- Lifetime Warranty / Made in the U.S.A.

Technical Specifications

Input Voltage	115VAC, 50/60Hz, 2.0A or 230VAC, 50/60Hz, 1A.
Output	Output options: a. 7.25A @ 24VAC or b. 6.25A @ 28VAC.
Indicators (LED)	Individual power output LED indicators. Illuminated master power switch.
Agency Listings	UL/cUL: Information Technology Equipment (UL 60950-1) Equipment to be Installed Outdoors (UL 60950-22). CE European Conformity
Enclosure Dimensions (H x W x D approx.):	13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm).
Product Weight / Shipping (approx.)	Product Weight: 13.12 lbs. (5.95 kg) Shipping Weight: 14.22 lbs. (6.45 kg)
Temperature	Operating: 24VAC @ 7.25A output: - 40°C to 60°C (-40°F to 140°F); 28VAC @ 6.25A output: - 40°C to 70°C (-40°F to 158°F). Storage: -40°C to 75°C (-40°F to 167°F).
Relative Humidity	85% +/-5%
BTU/Hr. (approx.):	90 BTU/Hr.

Product Codes

Part Code	Description
VAR-PSU-7A4U	Outdoor AC Power Supplies

Accessories

VAR-PSU-PMK1 Pole Mount Kit (order separately)

VAR-PSU-PMK1 pole mount kit is designed to simplify installation of outdoor units. It accommodates 2"- 8"(diameter) poles.

Kit includes:

- Two (2) powder coated steel mount brackets.
- Four (4) stainless steel bolts.
- Four (4) stainless steel lock washers.
- Two (2) wormgear quick release straps.

